

Product designation**Lightbar 60 Evolution**

Article no. 32.351.XX

Product description

Light with dimensions 58 x 12 cm (22.8 x 4.7 inches), can be operated at up to 1 x 3200 J, "tunnel-shaped" plexiglass diffuser, sheet steel back with cable outlet, 5 meter (16.4 ft) cable, modelling light switch, and separate interchangeable tilt head.

Scope of delivery

Lightbar with one cable, flash tubes, modelling lamps and interchangeable tilt head.

Technical data

Flash energy	1 x 3200 J
F-stop at 2 m (6 ½ ft), 100 ISO	32 5/10
Modelling light	220 V 10 x 20 W / 24 V
	110 V 10 x 20 W / 12 V
Cable length	1 x 5 m (16.4 ft.)
Cooling	1 fan
Dimensions	58 x 12 x 13 cm / 22.8 x 4.7 x 5.1 inches
Weight	3.6 kg / 8 lb

Compatibility

Power packs	Grafit 2, 4, A2, A4, A2 RFS, A4 RFS, A8 RFS, A2 plus, A4 plus, Topas A2, A4, A8 Nano 2, Mobil, Mobil A2 R Pulso 2, A2, 4, A4, Opus 2, A2, 4, A4, A8, Primo, Primo A, Primo A fashion, Primo 4,
-------------	---

For heat-related reasons, it is not possible to equip the Lightbar with a proportional halogen modelling lamp matching the other lamps.

Accessories

- Art. no. 33.272.00 Plexi cap mat for Lightbar 60 Evolution
- Art. no. 33.228.00 Barn door for Lightbar/Striplite 60 Evolution
- Art. no. 33.274.00 Striplite adapter for Lightbar 60 Evolution
- Art. no. 33.217.00 Honeycomb grid for Striplite 60 Evolution

Application

Background gradations and general gradations - Automobile and bus lighting - Mirror projection of lines - Outlining contours and edges - Deep objects (depth) as in cupboards, deep-freezers, car boots etc. can be lit in the simplest way - Several Lightbars can be placed together for uninterrupted lighting - Simple and versatile mounting with the interchangeable tilt head - The possibility of transforming the Lightbar into a Striplite increases the application range.