

Product designation

Minipuls C200

Article no. 31.449.XX

Product description

Monolight with Pulso bayonet, 1500 J flash energy, 4 f-stops continuous with rotary knob, built-in photocell and infrared receiver (can be switched off individually), proportional or full modelling light, internal discharge when power setting is reduced, dim-function of the modelling light

Scope of delivery

Unit with mains cable and protection cap, operating instructions

Flash tube, modelling lamp and protecting glass have to be ordered separately.

Technical data

Flash energy	1500 J
F-stop at 2 m / 6.6 feet, 100 ISO, P50 // P70	90 // 64
Flash duration t 0.1 (t 0.5)	1/250 s (1/1000 s)
Charging time (for 100 % of selected energy) ¹⁾	0.6 - 2.4 s
Ready display	visual with two-coloured LED, at 100 % of selected energy
Control range continuous	4 f-stops with rotary knob
Halogen modelling light	300-650 W with 220-240 V 150-300 W with 110-120 V
Flash release	wireless via infrared transmitter IRX 2, FCM 2 ²⁾ , FCC ²⁾ , photocell, synchronous cable, manual test button
Stabilized flash voltage	+/- 1 %
Standards	73/23/CEE and 89/336/CEE
Power requirements ³⁾	200-240 V, 50-60 Hz, 10 A or 110-120 V, 50-60 Hz, 16 A 100 V version not available
Cooling	fan
Dimensions	120 x 195 x 495 mm / 4.7 x 7.7 x 19.5 inch
Weight	4.5 kg / 9.9 lb

1) measured with 230 V / 50 Hz, resp. 120 V / 60 Hz

2) from year of production 1995, serial number begins with C (= compatible with Minipuls C), recommended for smaller rooms only.

Data sheet broncolor

- 3) the units work only with one voltage and are not switchable. However, the version 220-240 V works with the following restrictions to 120 V / 60 Hz: A modelling light 120 V / 150 W has to be applied, the charging time increases to 6.9 s.

Compatibility

Light shaper	all broncolor light shapers
IR triggering	IRX 2 FCC ²⁾ , FCM 2 ²⁾ (channel "9" see operating instructions FCM 2) The infrared triggering is guaranteed only with meters produced after 1/95 (serial number begins with C).

Accessories

Minipuls Location Kit 2 5500 K	Art. no. 31.454.XX
Minipuls Location Kit 3 5500 K	Art. no. 31.456.XX
Flash tube 5900 K to Minipuls C200	Art. no. 34.310.00
Halogen modelling light 300 W / 120 V	Art. no. 34.225.XX
Halogen modelling light 650 W / 240 V	Art. no. 34.226.XX
Protecting glass, clear 5500 K	Art. no. 34.336.00
Protecting glass, mat 5500 K	Art. no. 34.337.00
Fuse 3.15 AF	Art. no. 37137.00
Transport protection cap, grey	Art. no. Z3620.00
Mains cable Europe 200-240 V	Art. no. 39086.00
Mains cable CH 200-240 V	Art. no. 39084.00
Mains cable USA 100-120 V	Art. no. 39085.00

Application

All types of flash photography, but especially for people and location photography.